

04.04.2016

" - " ( )						
		(EN 1433)	100 000 .	200 000 .	200 000 .	
<b>100 ( 15 - 250)</b>						
	4010	DN 100 60 (500 140 60)	-	258	240	225
	401009 *	DN 100 60 (500 140 60)	-	600	568	530
	4000	DN 100 130 (1000 140 130)	-	438	410	380
	400009 *	DN 100 130 (1000 140 130)	-	788	735	690
<b>100 ( 15 - 250)</b>						
	4080	DN 100 (500 140 390)	-	2 100	1 977	1 765
<b>100 ( 15 - 250)</b>						
	2010	DN 100 (1000 136 3)	-	375	330	310
	20101	DN 100 (1000 136 3)	-	375	330	310
	20901	DN 100 (1000 136 3)	-	1 426	1 273	1 171
	20801	DN 100 (1000 136 3)	-			
	202026	DN 100 (1000 136 3)	-	1 158	1 015	955
	203032	DN 100 (500 136 15)	-	478	427	393
PROTEKTOR	20303	DN 100 (500 136 15)	-	430	400	380
	203036	DN 100 (500 136 15)	-	680	640	600
	20403	DN 100 (500 136 15)	-	478	427	393
	204036	DN 100 (500 136 16)	-	680	640	600
<b>100 ( 15 - 250)</b>						
	6102	100 40 35	-	85	80	75
	6160	1000 23 25	-	140	130	120
	6101	141 125	-	141	134	120

	A 15 ( 15 KN)
	B 125 ( 125 KN)
	C 250 ( 250 KN)
	D 400 ( 400 KN)
	E 600 ( 600 KN)

EN 1433, EN 124, 3634-99:

